

- 1
- 2
- 3
- 4
- 5
- 6
- 7
- 8
- 9
- 10
- 11
- 12
- 13
- 14
- 15
- 16
- 17
- 18
- 19
- 20
- 21
- 22
- 23
- 24
- 25
- 26
- 27
- 28
- 29

1. A railroad e-clip removal system, comprising:
 - an outer tube with an outer cutout;
 - an inner tube slidably positioned within a lumen of said outer tube, wherein said inner tube includes an inner cutout and an engaging portion, wherein said engaging portion is engageable to an e-clip; and
 - an actuator unit attached to said outer tube, wherein said actuator unit includes a shaft member that is attached to said inner tube for extending/retracting said inner tube within said outer tube.

3. The railroad e-clip removal system of Claim 1, wherein said engaging portion is positioned near a rear portion of said outer cutout when said inner tube is retracted.

5. The railroad e-clip removal system of Claim 1, wherein said outer tube and said outer tube have a similar cross sectional shape.

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29

6. The railroad e-clip removal system of Claim 1, including a plurality of legs attached to said outer tube.

7. The railroad e-clip removal system of Claim 6, wherein one of said legs is engageable to a tubular support member during removal of an e-clip.

8. The railroad e-clip removal system of Claim 6, wherein one of said legs is shorter than the remaining legs and has a flanged portion for being positioned upon a rail foot of a rail member.

9. The railroad e-clip removal system of Claim 1, wherein said outer tube is longer than said inner tube.

10. The railroad e-clip removal system of Claim 1, wherein said outer cutout and said inner cutout are similar in position and size.

11. A railroad e-clip removal system, comprising:
an outer tube with an outer cutout;
a support structure having a handle member attached to said outer tube;
an inner tube slidably positioned within a lumen of said outer tube, wherein said inner tube includes an inner cutout and an engaging portion, wherein said engaging portion is engageable to an e-clip; and

1 an actuator unit attached to said outer tube, wherein said actuator unit includes
2 a shaft member that is attached to said inner tube for extending/retracting said inner
3 tube within said outer tube.

4
5
6 12. The railroad e-clip removal system of Claim 11, wherein said engaging
7 portion is a lower rear edge of said inner cutout.

8
9
10 13. The railroad e-clip removal system of Claim 11, wherein said engaging
11 portion is positioned near a rear portion of said outer cutout when said inner tube is
12 retracted.

13
14
15 14. The railroad e-clip removal system of Claim 11, wherein said engaging
16 portion extends below said outer cutout for engaging an e-clip.

17
18
19 15. The railroad e-clip removal system of Claim 11, wherein said outer tube
20 and said outer tube have a similar cross sectional shape.

21
22
23 16. The railroad e-clip removal system of Claim 11, including a plurality of
24 legs attached to said outer tube.

25
26
27 17. The railroad e-clip removal system of Claim 16, wherein one of said legs is
28 engageable to a tubular support member during removal of an e-clip.

1

2 18. The railroad e-clip removal system of Claim 16, wherein one of said legs is
3 shorter than the remaining legs and has a flanged portion for being positioned upon a
4 rail foot of a rail member.

5

6

7 19. The railroad e-clip removal system of Claim 11, wherein said outer tube is
8 longer than said inner tube.

9

10

11 20. A method of operating a railroad e-clip removal apparatus for removing an
12 e-clip, wherein said railroad e-clip removal apparatus is comprised of an outer tube
13 with an outer cutout, an inner tube slidably positioned within a lumen of said outer
14 tube, wherein said inner tube includes an inner cutout and an engaging portion,
15 wherein said engaging portion is engageable to an e-clip, and an actuator unit attached
16 to said outer tube, wherein said actuator unit includes a shaft member that is attached
17 to said inner tube for extending/retracting said inner tube within said outer tube, said
18 method comprising the steps of:

19 (a) positioning said railroad e-clip removal apparatus about an e-clip
20 positioned within a tubular support member, wherein said e-clip is positioned beneath
21 said inner cutout; and

22 (b) extending said actuator unit so that said inner tube extends forwardly
23 within said outer tube and wherein said engaging portion engages said e-clip for
24 removing said e-clip from said tubular support member.